



**Size:** Amm × Bmm × Cmm

**Motor:** Capacitor induction

**Bearing:** Ball

**Impeller:** Aluminum

**Frame:** Metal

**Life:** 30000hours

**Operation Temperature:** -20°C ~ +60°C

Model	A	B	C	D	E
GF-470-110	470	150	150	100	425
GF-580-110	580	150	150	100	530
GF-480-125	480	175	200	145	435
GF-590-125	590	175	200	145	540
GF-500-150	500	200	220	160	445
GF-600-150	600	200	220	160	550
GF-600-200	600	270	270	200	550

Model	Voltage VAC	Phase	Freq. Hz	Current A	Power W	Speed RPM	Air flow m <sup>3</sup> /hr	Noise dB	Amount/Cover	Transformer KVA
GF-470-110	220/380	Single-Phase/3P	50	0.30/0.20	55	1400	550	52	6	630-800
GF-580-110				0.30/0.20	60	1400	680	52	4	400-650
GF-480-125				0.40/0.22	75	1400	700	52	4	800-1000
GF-590-125				0.40/0.22	80	1400	850	53	4	800-1200
GF-500-150				0.40/0.22	85	1400	1200	54	6	800-1600
GF-600-150				0.50/0.30	100	1400	1500	55	6	1600-2000
GF-600-200				1.40/0.50	300	1400	2500	65	6	2000-3000